

PRODUCTION OF LIQUID CRYSTAL DISPLAY ELEMENT

Patent Number: JP10177178
Publication date: 1998-06-30
Inventor(s): MIYATA SHINICHI; TANAKA YOSHINORI; YAMAZAKI ATSUSHI
Applicant(s): MATSUSHITA ELECTRIC IND CO LTD
Requested Patent: ☐ JP10177178
Application Number: JP19960336187 19961217
Priority Number(s):
IPC Classification: G02F1/1341
EC Classification:
Equivalents:

Abstract

PROBLEM TO BE SOLVED: To decrease the reaction between amines and a liquid crystal having dielectric anisotropy and to decrease display defects by adding a process for temporarily hardening a sealing material by irradiation with energy prior to a process to drop a liquid crystal.
SOLUTION: A sealing material 2 comprising an acryl resin material is printed on a glass substrate 1 with an ITO electrode being a transparent electrode. The sealing material 2 is temporarily hardened by irradiation with IR rays 3 as the energy for irradiation, and then a liquid crystal material 4 having dielectric anisotropy is dropped onto the area surrounded by the temporarily hardened sealing material. After laminating, the sealing material 2 is again completely hardened by irradiation of energy 6. In the obtd. liquid crystal display element, amines in the sealing material 2 are decreased to a half amt. and the reaction with the liquid crystal 4 is decreased by half because the sealing material 2 is temporarily processed when the liquid crystal 4 is dropped, and therefore, display defects can be decreased.

Data supplied from the esp@ccnet database - I2